



## SPECIFICATIONS

|  |                 |                                             |
|--|-----------------|---------------------------------------------|
|  | <b>GEOLOGY</b>  | Sandstone                                   |
|  | <b>TYPE</b>     | 100% Bedface                                |
|  | <b>PATTERN</b>  | 2:1 Dimensional Ashlar or Coursed           |
|  | <b>HEIGHTS</b>  | 2-1/2", 5"                                  |
|  | <b>LENGTHS</b>  | 6" - 24"                                    |
|  | <b>DEPTHS</b>   | 3/4" to 1-1/4"                              |
|  | <b>COLORS</b>   | Gray-Grey                                   |
|  | <b>COVERAGE</b> | Available in thin veneer only.              |
|  | <b>WEIGHT</b>   | 12.5 lbs per square foot                    |
|  | <b>FLATS</b>    | 10 s/f Box, 100 s/f Crate, 180 s/f Crate    |
|  | <b>CORNERS</b>  | 10 ln/ft Box, 100 ln/ft Crate               |
|  | <b>NOTES</b>    | Packaged assuming a tight-fit installation. |

### ASTM C-97

|                       |          |
|-----------------------|----------|
| Water Absorption %    | .12 psi  |
| Bulk Specific Gravity | 2.78 psi |

### ASTM C-170

|                            |           |
|----------------------------|-----------|
| Parallel to Rift, Dry      | 14214 psi |
| Parallel to Rift, Wet      | 14213 psi |
| Perpendicular to Rift, Dry | 21814 psi |
| Perpendicular to Rift, Wet | 21320 psi |

### ASTM C-99

|                       |          |
|-----------------------|----------|
| Parallel to Rift, Dry | 3046 psi |
| Parallel to Rift, Wet | 3191 psi |

### ASTM C-880

|                            |          |
|----------------------------|----------|
| Perpendicular to Rift, Dry | 4351 psi |
| Perpendicular to Rift, Wet | 4351 psi |

Fond du Lac Natural Stone | [fdlnaturalstone.com](http://fdlnaturalstone.com)  
N4224 Hwy 175 PO Box 347 Fond du Lac, WI 54936-0347  
Phone: 920-923-2800 | Toll Free: 877-923-2800 | Fax: 920-923-3800

